

OXC-2100 α – OSHIROX Anti-graffiti agent –

【Product Details】

OXC-2100 α is solvent-based one-component paint with anti-graffiti and anti-affixing functions mainly composed of silicone. This paint is applicable to concrete and natural stone. And this paint can also be applied to glass, metal, wood, plastic, etc. by applying a primer. Installation is easy because it is a one-component paint and a one-time coat. This coating film lasts for a long time, and even if the coating film is worn by repeated graffiti removal, it can be repaired by applying the same paint on top of each other. Spray, magic, etc. graffiti can be removed using water wipes or high-pressure washing. In addition, posters and stickers attached to this coating film can be easily removed. Even after graffiti is removed, the performance is maintained until the paint film wears out, so there is no need to repaint. This coating film exhibits excellent vapor permeability and is less prone to coating film problems such as blistering, peeling, and cracking. It forms a colorless and glossy coating film, but the color and texture may change due to the suction of the material, so it is recommended to test it in a small range in advance.

【Product properties】

Product Name	OXC-2100 α – OSHIROX Anti-graffiti agent –
Appearance	milky liquid
Principal component	Silicone Elastomer
Classification	Flammable liquids Category 4 Petroleum No. 2 (Water-insoluble liquid) Hazard Class: III.
Storability	12months (Store sealed below 30°C)
Usage	Measures to prevent graffiti on stone and concrete (Graffiti can be easily removed) Prevent sticking of posters and stickers

【Packing】

OXC-2100 α 1Kg／4Kg／15Kg

The contents of this catalog are subject to change without notice for performance improvement and specification changes.

OSHIROX Corporation

head office

〒559-0011 Osaka-fu, Osaka-shi, Suminoe-ku, Kitakagaya, 4-1-55

E-mail : info@oshirox.jp

Web : <http://oshirox.jp>

manufacturer

〒635-0032 Hyogo-ken, Kobe-shi, Nagata-ku, Karimodori 1-3-17

【Standard coating volume】

It depends on the type of stone or concrete, the temperature, and the degree of dryness of the material, but it should be about 200~300g/m².

【Cleaning methods】

Remove mud stains, oil stains, scale, etc. adhering to stone or concrete with our cleaning agent suitable for dirt, wash it carefully with water, and dry it thoroughly before painting.

【How to use】

- Apply with a brush, roller or spray.
- When using a spray, dilute with the specified diluent so that it is easy to apply.
- It takes about 4 hours to dry to the touch and about 24 hours to fully cure.

【After curing】

- To remove graffiti, rub it with a rag, sponge, tissue, etc. soaked in water. If you rub it with a hard object such as a dry cloth, the coating film may peel off.
- You can also use a pressure washer to remove graffiti.

【Usage notes】

1. Please read this manual carefully before use.
2. Mud, oil, and scale on stone or concrete interfere with the penetration and adhesion of the coat, so be sure to wash it with our detergent and dry it well before use.
3. Wear rubber gloves and glasses while working, especially careful not to get them in your eyes.
4. Be sure to test on a sample to see changes in hue and texture.
5. Since it falls under the category of Class 4 petroleum No.2 non-soluble liquid of the Fire Service Act, it is necessary to store and handle it in accordance with the law.
6. When diluting, please dilute with our designated diluent.
7. The curing time is about 12 hours, but it varies depending on the temperature and humidity.
8. Store the paint in a closed state in a cool, dark place below 30° C.
9. Keep the container cap tightly tightened except when handling the product.
10. Remove from the container only as much as you need and do not return the used remainder to the container.
11. Do not use the product in conjunction with other companies' products, as the performance of this product will be hindered if used in conjunction with other companies' products.
12. The brushes and rollers used should be dedicated to this product or disposable. After cleaning the brush and roller used to paint this product, avoid using it for other paints. Spray and other equipment should be thoroughly cleaned with thinner.
13. If there are trees or flowers around the enforcement site, do not scatter the product.
14. Please refer to the Safety Data Sheet (SDS) for usage notes and details.